# 2001 HONDA XR650R

Maintenance schedule · tick each job as it's done

## TIMELINE · MILES ON THE METER

**100 mi**
- ☐ Change engine oil *(first)*
- ☐ Change oil filter *(first)*

DATE _____ MILES _____

**600 mi**
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

**1,200 mi**
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

**1,800 mi**
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

**2,400 mi**
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

**3,000 mi**
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

**3,600 mi**
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

## SCHEDULE

**Change engine oil**
First at 100 mi or 1 month, then every 600 mi or 6 months

**Change oil filter**
First at 100 mi or 1 month, then every 600 mi or 6 months

**Clean air filter**
Every 600 mi or 6 months

**Inspect spark plug**
Every 600 mi or 6 months

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with Honda and accepts no liability for use of this sheet (findmydirtbike.com/terms).

# 2001 HONDA XR650R

Garage specs: fluids, plug, chain, tires and torques

## FLUIDS

| | |
|---|---|
| Oil type | 20W-50 (10W-40 below 32°F) |
| Engine oil | 1.65 US qt (1.56 L) |
| Coolant | 1.82 US qt (1.72 L) |
| Fuel capacity | 2.6 gal |

## SPARK PLUG

| | |
|---|---|
| Spark plug | NGK BKR7E-11 |
| Plug gap | 0.039 - 0.043 in (1.00 - 1.10 mm) |
| Spark plug (alternative) | DENSO K22PR-U11 |
| Spark plug (extended high speed riding) | NGK BKR8E-11 |
| Spark plug (extended high speed riding, alternative) | DENSO K24PR-U11 |

## CHAIN, SPROCKETS & TIRES

| | |
|---|---|
| Chain size | 520 |
| Front sprocket | 14T |
| Rear sprocket | 48T |
| Front tire | 80/100-21 |
| Rear tire | 110/100-18 |

## TORQUE SPECS

| | |
|---|---|
| Oil drain bolt (crankcase) | 18 ft-lb (25 N·m, 2.5 kgf·m) |
| Oil drain bolt (frame) | 19 ft-lb (26 N·m, 2.7 kgf·m) |
| Oil filter cover bolts | 8.9 ft-lb (12 N·m, 1.2 kgf·m) |
| Front axle | 65 ft-lb (88 N·m, 9.0 kgf·m) |
| Front axle pinch nuts | 8.9 ft-lb (12 N·m, 1.2 kgf·m) |
| Rear axle nut | 69 ft-lb (93 N·m, 9.5 kgf·m) |

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with Honda and accepts no liability for use of this sheet (findmydirtbike.com/terms).