2010 KTM 125 SX

Maintenance schedule · tick each job as it's done

TIMELINE · HOURS ON THE METER

		DATE	HOURS
10 h	☐ Change gearbox oil *(first)* ☐ Clean air filter *(first)* ☐ Inspect spark plug *(first)*		
20 h	☐ Inspect gearbox oil, spark plug & piston and rings ☐ Clean air filter		
40 h	☐ Change gearbox oil ☐ Inspect gearbox oil, spark plug & piston and rings ☐ Clean air filter		
60 h	☐ Inspect gearbox oil, spark plug & piston and rings ☐ Clean air filter		
80 h	☐ Change gearbox oil ☐ Inspect gearbox oil, spark plug & piston and rings ☐ Clean air filter		
100 h	☐ Inspect gearbox oil, spark plug & piston and rings ☐ Clean air filter		
120 h	☐ Change gearbox oil ☐ Inspect gearbox oil, spark plug & piston and rings ☐ Clean air filter		

SCHEDULE

Change gearbox oil
`First at 10 h, then every 40 hours or after every race`

Clean air filter
`First at 10 h, then every 20 hours`

Inspect spark plug
`First at 10 h`

Inspect gearbox oil, spark plug & piston and rings
`Every 20 hours`

EVERY RIDE & BY THE CALENDAR

- ☐ **Clean air filter** · Every race
- ☐ **Inspect spark plug** · Every race

HARDER RIDING: SERVICE SOONER

Difficult operating conditions: check the air filter approx. every 30 minutes

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with KTM and accepts no liability for use of this sheet (findmydirtbike.com/terms).

2010 KTM 125 SX

Garage specs: fluids, plug, chain, tires and torques

FLUIDS

Gearbox oil type	Engine oil (15W/50)
Gearbox oil	0.74 US qt (0.7 L)
Engine lubrication	Premix (oil in the fuel)
Premix ratio	40:1 (fuel to oil)
2-stroke oil	2-stroke engine oil (JASO FC)
Coolant	1.3 US qt (1.2 L)
Fuel capacity	2.1 gal

SPARK PLUG

Spark plug	NGK BR9 ECMVX
Plug gap	0.024 in (0.60 mm)

CHAIN, SPROCKETS & TIRES

Chain size	520
Front sprocket	13T
Rear sprocket	50T
Front tire	Bridgestone M59 80/100-21 51M TT
Rear tire	Bridgestone M70 100/90-19 57M TT

TORQUE SPECS

Gearbox oil drain plug (M10x1)	11 ft-lb (15 N·m)
Gearbox oil drain plug (M12x1.5, with magnet)	15 ft-lb (20 N·m)
Spark plug	18 ft-lb (25 N·m)
Front axle	33 ft-lb (45 N·m)
Front axle pinch bolts	11 ft-lb (15 N·m)
Rear axle nut	59 ft-lb (80 N·m)
Upper triple clamp bolts	13 ft-lb (17 N·m)
Lower triple clamp bolts	8.9 ft-lb (12 N·m)
Steering stem bolt	7.4 ft-lb (10 N·m)
Handlebar clamp bolts	15 ft-lb (20 N·m)
Front brake caliper mounting bolts	18 ft-lb (25 N·m)
Front brake disc bolts	10 ft-lb (14 N·m)
Rear brake disc bolts	10 ft-lb (14 N·m)
Rear sprocket nuts	26 ft-lb (35 N·m)
Shock absorber bottom mount	59 ft-lb (80 N·m)
Shock absorber top mount	59 ft-lb (80 N·m)
Coolant drain bolt	11 ft-lb (15 N·m)

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with KTM and accepts no liability for use of this sheet (findmydirtbike.com/terms).