2025 KTM 250 XC-F

Maintenance schedule · tick each job as it's done

TIMELINE · HOURS ON THE METER

		DATE	HOURS
1 h	☐ Change engine oil & oil filter *(first)*		
15 h	☐ Change engine oil & oil filter ☐ Clean air filter		
30 h	☐ Change engine oil & oil filter ☐ Clean air filter		
45 h	☐ Change engine oil & oil filter ☐ Clean air filter ☐ Change spark plug & piston and rings		
60 h	☐ Change engine oil & oil filter ☐ Clean air filter		
75 h	☐ Change engine oil & oil filter ☐ Clean air filter		
90 h	☐ Change engine oil & oil filter ☐ Clean air filter ☐ Change spark plug & piston and rings		

SCHEDULE

Change engine oil & oil filter
`First at 1 h, then every 15 hours or 24 months`

Clean air filter
`Every 15 hours or 24 months`

Change spark plug & piston and rings
`Every 45 hours`

HARDER RIDING: SERVICE SOONER

Difficult operating conditions: check the air filter approx. every 30 minutes

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with KTM and accepts no liability for use of this sheet (findmydirtbike.com/terms).

2025 KTM 250 XC-F

Garage specs: fluids, plug, chain, tires and torques

FLUIDS

Oil type	10W/50
Engine oil	1.1 US qt (1.0 L)
Coolant	1.00 US qt (0.95 L)
Fuel capacity	2.25 gal

SPARK PLUG

Spark plug	NGK LMAR9AI-10
Plug gap	0.039 in (1.0 mm)

CHAIN, SPROCKETS & TIRES

Chain size	520
Front sprocket	13T
Rear sprocket	52T
Front tire	Dunlop Geomax MX33F 80/100-21 51M
Rear tire	Dunlop Geomax AT81 110/100-18 64M

TORQUE SPECS

Oil drain bolt	15 ft-lb (20 N·m)
Oil filter cover bolts	7.4 ft-lb (10 N·m)
Spark plug	8.9 ft-lb (12 N·m)
Front axle	26 ft-lb (35 N·m)
Front axle pinch bolts	11 ft-lb (15 N·m)
Rear axle nut	59 ft-lb (80 N·m)
Upper triple clamp bolts	13 ft-lb (17 N·m)
Lower triple clamp bolts	8.9 ft-lb (12 N·m)
Steering stem bolt	8.9 ft-lb (12 N·m)
Handlebar clamp bolts	15 ft-lb (20 N·m)
Front brake caliper mounting bolts	18 ft-lb (25 N·m)
Front brake disc bolts	10 ft-lb (14 N·m)
Rear brake disc bolts	10 ft-lb (14 N·m)
Rear sprocket nuts	26 ft-lb (35 N·m)
Front sprocket bolt	44 ft-lb (60 N·m)
Shock absorber bottom mount	44 ft-lb (60 N·m)
Shock absorber top mount	44 ft-lb (60 N·m)

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with KTM and accepts no liability for use of this sheet (findmydirtbike.com/terms).