2011 KTM 250 XC-W

Maintenance schedule · if used in sand regularly · tick each job as it's done

TIMELINE · HOURS ON THE METER

		DATE	HOURS
10 h	☐ Change piston		
20 h	☐ Change gearbox oil & spark plug ☐ Clean air filter ☐ Change piston		
30 h	☐ Change piston		
40 h	☐ Change gearbox oil & spark plug ☐ Clean air filter ☐ Change piston		
50 h	☐ Change piston		
60 h	☐ Change gearbox oil & spark plug ☐ Clean air filter ☐ Change piston		
70 h	☐ Change piston		
80 h	☐ Change gearbox oil & spark plug ☐ Clean air filter ☐ Change piston		
90 h	☐ Change piston		
100 h	☐ Change gearbox oil & spark plug ☐ Clean air filter ☐ Change piston		
110 h	☐ Change piston		
120 h	☐ Change gearbox oil & spark plug ☐ Clean air filter ☐ Change piston		
130 h	☐ Change piston		
140 h	☐ Change gearbox oil & spark plug ☐ Clean air filter ☐ Change piston		

SCHEDULE

Change piston
Every 10 hours

Change gearbox oil & spark plug
Every 20 hours

Clean air filter
Every 20 hours

EVERY RIDE & BY THE CALENDAR

- ☐ **Change gearbox oil** · Every race
- ☐ **Clean air filter** · Every race
- ☐ **Change spark plug** · Every race

HARDER RIDING: SERVICE SOONER

After sporting use · every 40 hours: change piston

Difficult operating conditions: check the air filter approx. every 30 minutes

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with KTM and accepts no liability for use of this sheet (findmydirtbike.com/terms).

2011 KTM 250 XC-W

Garage specs: fluids, plug, chain, tires and torques

FLUIDS

Gearbox oil type	Engine oil (15W/50)
Gearbox oil	0.85 US qt (0.8 L)
Engine lubrication	Premix (oil in the fuel)
Premix ratio	60:1 (fuel to oil)
2-stroke oil	2-stroke engine oil (JASO FC)
Coolant	1.3 US qt (1.2 L)
Fuel capacity	3.04 gal

SPARK PLUG

Spark plug	NGK BR 7 ES
Plug gap	0.0236 in (0.60 mm)

CHAIN, SPROCKETS & TIRES

Chain size	520
Front sprocket	13T
Rear sprocket	50T
Front tire	Bridgestone M59 80/100-21 51M TT
Rear tire	Bridgestone M402 110/100-18 64M TT

TORQUE SPECS

Gearbox oil drain plug	15 ft-lb (20 N·m)
Spark plug	18 ft-lb (25 N·m)
Front axle	33 ft-lb (45 N·m)
Front axle pinch bolts	11 ft-lb (15 N·m)
Rear axle nut	59 ft-lb (80 N·m)
Upper triple clamp bolts	13 ft-lb (17 N·m)
Lower triple clamp bolts	8.9 ft-lb (12 N·m)
Steering stem bolt	7.4 ft-lb (10 N·m)
Handlebar clamp bolts	15 ft-lb (20 N·m)
Front brake caliper mounting bolts	18 ft-lb (25 N·m)
Front brake disc bolts	10 ft-lb (14 N·m)
Rear brake disc bolts	10 ft-lb (14 N·m)
Rear sprocket nuts	26 ft-lb (35 N·m)
Shock absorber mounting bolts	59 ft-lb (80 N·m)
Coolant drain bolt	11 ft-lb (15 N·m)

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with KTM and accepts no liability for use of this sheet (findmydirtbike.com/terms).