2025 KTM 450 XC-F

Maintenance schedule · tick each job as it's done

TIMELINE · HOURS ON THE METER

		DATE	HOURS
1 h	☐ Change engine oil & oil filter *(first)*		
15 h	☐ Change engine oil & oil filter ☐ Clean air filter		
30 h	☐ Change engine oil & oil filter ☐ Clean air filter		
45 h	☐ Change engine oil & oil filter ☐ Clean air filter ☐ Change spark plug & piston and rings		
60 h	☐ Change engine oil & oil filter ☐ Clean air filter		
75 h	☐ Change engine oil & oil filter ☐ Clean air filter		
90 h	☐ Change engine oil & oil filter ☐ Clean air filter ☐ Change spark plug & piston and rings		

SCHEDULE

Change engine oil & oil filter
`First at 1 h, then every 15 hours or 24 months`

Clean air filter
`Every 15 hours or 24 months`

Change spark plug & piston and rings
`Every 45 hours`

HARDER RIDING: SERVICE SOONER

Difficult operating conditions: check the air filter approx. every 30 minutes

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with KTM and accepts no liability for use of this sheet (findmydirtbike.com/terms).

2025 KTM 450 XC-F

Garage specs: fluids, plug, chain, tires and torques

FLUIDS

Oil type	**10W/50**
Engine oil	**1.3 US qt (1.2 L)**
Coolant	**1.00 US qt (0.95 L)**
Fuel capacity	**2.25 gal**

SPARK PLUG

Spark plug	**NGK LMAR9AI-10**
Plug gap	**0.039 in (1.0 mm)**

CHAIN, SPROCKETS & TIRES

Chain size	**520**
Front sprocket	**13T**
Rear sprocket	**52T**
Front tire	**Dunlop Geomax MX33F 80/100-21 51M TT**
Rear tire	**Dunlop Geomax AT81 110/100-18 64M TT**

TORQUE SPECS

Oil drain bolt	**15 ft-lb (20 N·m)**
Oil filter cover bolts	**7.4 ft-lb (10 N·m)**
Spark plug	**7.4–8.9 ft-lb (10–12 N·m)**
Front axle	**26 ft-lb (35 N·m)**
Front axle pinch bolts	**11 ft-lb (15 N·m)**
Rear axle nut	**59 ft-lb (80 N·m)**
Upper triple clamp bolts	**13 ft-lb (17 N·m)**
Lower triple clamp bolts	**8.9 ft-lb (12 N·m)**
Steering stem bolt	**8.9 ft-lb (12 N·m)**
Handlebar clamp bolts	**15 ft-lb (20 N·m)**
Front brake caliper mounting bolts	**18 ft-lb (25 N·m)**
Front brake disc bolts	**10 ft-lb (14 N·m)**
Rear brake disc bolts	**10 ft-lb (14 N·m)**
Rear sprocket nuts	**26 ft-lb (35 N·m)**
Front sprocket bolt	**44 ft-lb (60 N·m)**
Shock absorber top mount	**44 ft-lb (60 N·m)**
Shock absorber bottom mount	**44 ft-lb (60 N·m)**

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with KTM and accepts no liability for use of this sheet (findmydirtbike.com/terms).