2026 YAMAHA WR450F

Maintenance schedule · tick each job as it's done

TIMELINE · MILES ON THE METER

600 mi
- ☐ Change engine oil *(first)*
- ☐ Change oil filter *(first)*
- ☐ Clean and oil air filter *(first)*
- ☐ Inspect spark plug *(first)*

DATE _____ MILES _____

1,200 mi
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean and oil air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

2,400 mi
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean and oil air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

3,600 mi
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean and oil air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

4,800 mi
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean and oil air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

6,000 mi
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean and oil air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

7,200 mi
- ☐ Change engine oil
- ☐ Change oil filter
- ☐ Clean and oil air filter
- ☐ Inspect spark plug

DATE _____ MILES _____

SCHEDULE

Change engine oil
First at 600 mi or 1 month, then every 1,200 mi or 3 months

Change oil filter
First at 600 mi or 1 month, then every 1,200 mi or 3 months

Clean and oil air filter
First at 600 mi or 1 month, then every 1,200 mi or 3 months

Inspect spark plug
First at 600 mi or 1 month, then every 1,200 mi or 3 months

HARDER RIDING: SERVICE SOONER

Competition use · every 5 races or 1,000 km: change engine oil, replace oil filter, inspect piston, replace piston rings

Competition use · every race: clean and oil air filter

Competition use · every 3 races or 500 km: inspect spark plug

Competition use: after break-in

Competition use: after break-in

Competition use: after break-in

Competition use: after break-in

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with Yamaha and accepts no liability for use of this sheet (findmydirtbike.com/terms).

2026 YAMAHA WR450F

Garage specs: fluids, plug, chain, tires and torques

FLUIDS

Oil type	10W-40, 10W-50, 15W-40, 20W-40 or 20W-50
Engine oil	0.99 US qt (0.94 L)
Coolant	1.09 US qt (1.03 L)
Fuel capacity	2 gal

SPARK PLUG

Spark plug	NGK LMAR8G
Plug gap	0.028 – 0.031 in (0.7 – 0.8 mm)

CHAIN, SPROCKETS & TIRES

Chain size	520
Chain links	114
Front sprocket	13T
Rear sprocket	50T
Front tire	Dunlop Geomax MX33F 80/100-21 51M
Rear tire	Dunlop Geomax MX33 120/90-18 65M

TORQUE SPECS

Oil drain bolt (crankcase)	15 ft-lb (20 N·m, 2.0 kgf·m)
Oil tank drain bolt	7.4 ft-lb (10 N·m, 1.0 kgf·m)
Oil filter cover bolts	7.4 ft-lb (10 N·m, 1.0 kgf·m)
Spark plug	9.6 ft-lb (13 N·m, 1.3 kgf·m)
Front axle nut	85 ft-lb (115 N·m, 11.5 kgf·m)
Front axle pinch bolts	15 ft-lb (21 N·m, 2.1 kgf·m)
Rear axle nut	100 ft-lb (135 N·m, 13.5 kgf·m)
Upper triple clamp bolts	15 ft-lb (21 N·m, 2.1 kgf·m)
Lower triple clamp bolts	15 ft-lb (21 N·m, 2.1 kgf·m)
Steering stem nut	107 ft-lb (145 N·m, 14.5 kgf·m)
Handlebar clamp bolts	21 ft-lb (28 N·m, 2.8 kgf·m)
Front brake caliper mounting bolts	21 ft-lb (28 N·m, 2.8 kgf·m)
Front brake disc bolts	8.9 ft-lb (12 N·m, 1.2 kgf·m)
Rear brake disc bolts	8.9 ft-lb (12 N·m, 1.2 kgf·m)
Rear sprocket nuts	37 ft-lb (50 N·m, 5.0 kgf·m)
Front sprocket nut	66 ft-lb (90 N·m, 9.0 kgf·m)
Chain adjuster locknut	15 ft-lb (21 N·m, 2.1 kgf·m)
Shock absorber top mount	41 ft-lb (56 N·m, 5.6 kgf·m)
Shock absorber bottom mount	39 ft-lb (53 N·m, 5.3 kgf·m)
Coolant drain bolt	7.4 ft-lb (10 N·m, 1.0 kgf·m)

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with Yamaha and accepts no liability for use of this sheet (findmydirtbike.com/terms).