2007 YAMAHA YZ125

Maintenance schedule · tick each job as it's done

TIMELINE · HOURS ON THE METER

SCHEDULE

EVERY RIDE & BY THE CALENDAR

- ☐ **Change gearbox oil** · After break-in
- ☐ **Change gearbox oil** · Every 5 races
- ☐ **Clean and oil air filter** · After break-in
- ☐ **Clean and oil air filter** · Every race
- ☐ **Inspect and clean spark plug** · After break-in
- ☐ **Inspect and clean spark plug** · Every race
- ☐ **Inspect and clean piston** · After break-in
- ☐ **Inspect piston rings** · After break-in
- ☐ **Inspect and clean piston** · Every race
- ☐ **Replace piston** · Every 5 races
- ☐ **Inspect piston rings** · Every race
- ☐ **Replace piston rings** · Every 3 races

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with Yamaha and accepts no liability for use of this sheet (findmydirtbike.com/terms).

2007 YAMAHA YZ125

Garage specs: fluids, plug, chain, tires and torques

FLUIDS

Gearbox oil type	**10W-30**
Gearbox oil	**0.70 US qt (0.66 L)**
Engine lubrication	**Premix (oil in the fuel)**
Premix ratio	**30:1 (fuel to oil)**
2-stroke oil	**YAMALUBE 2-R**
Coolant	**0.95 US qt (0.9 L)**
Fuel capacity	**2.11 gal**

SPARK PLUG

Spark plug	**NGK BR9EVX**
Plug gap	**0.024 - 0.028 in (0.6 - 0.7 mm)**

CHAIN, SPROCKETS & TIRES

Chain size	**520**
Chain links	**112**
Front sprocket	**13T**
Rear sprocket	**48T**
Front tire	**80/100-21 51M**
Rear tire	**100/90-19 57M**

TORQUE SPECS

Gearbox oil drain bolt	**15 ft-lb (20 N·m, 2.0 kgf·m)**
Spark plug	**15 ft-lb (20 N·m, 2.0 kgf·m)**
Front axle nut	**77 ft-lb (105 N·m, 10.5 kgf·m)**
Front axle pinch bolts	**15 ft-lb (21 N·m, 2.1 kgf·m)**
Rear axle nut	**92 ft-lb (125 N·m, 12.5 kgf·m)**
Upper triple clamp bolts	**15 ft-lb (21 N·m, 2.1 kgf·m)**
Lower triple clamp bolts	**15 ft-lb (21 N·m, 2.1 kgf·m)**
Steering stem nut	**107 ft-lb (145 N·m, 14.5 kgf·m)**
Handlebar clamp bolts	**21 ft-lb (28 N·m, 2.8 kgf·m)**
Front brake caliper mounting bolts	**17 ft-lb (23 N·m, 2.3 kgf·m)**
Front brake disc bolts	**8.9 ft-lb (12 N·m, 1.2 kgf·m)**
Rear brake disc bolts	**10 ft-lb (14 N·m, 1.4 kgf·m)**
Rear sprocket nuts	**31 ft-lb (42 N·m, 4.2 kgf·m)**
Front sprocket nut	**55 ft-lb (75 N·m, 7.5 kgf·m)**
Chain adjuster locknut	**14 ft-lb (19 N·m, 1.9 kgf·m)**
Shock absorber top mount	**41 ft-lb (56 N·m, 5.6 kgf·m)**
Shock absorber bottom mount	**39 ft-lb (53 N·m, 5.3 kgf·m)**
Coolant drain bolt	**7.4 ft-lb (10 N·m, 1.0 kgf·m)**

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with Yamaha and accepts no liability for use of this sheet (findmydirtbike.com/terms).