2005 YAMAHA YZ250F

Maintenance schedule · tick each job as it's done

TIMELINE · HOURS ON THE METER

21 h
- ☐ Inspect and clean spark plug

DATE _____ HOURS _____

41 h
- ☐ Change engine oil
- ☐ Clean oil filter
- ☐ Change oil filter & piston rings
- ☐ Inspect piston

DATE _____ HOURS _____

42 h
- ☐ Inspect and clean spark plug

DATE _____ HOURS _____

63 h
- ☐ Inspect and clean spark plug

DATE _____ HOURS _____

82 h
- ☐ Change engine oil
- ☐ Clean oil filter
- ☐ Change oil filter & piston rings
- ☐ Inspect piston

DATE _____ HOURS _____

84 h
- ☐ Inspect and clean spark plug

DATE _____ HOURS _____

105 h
- ☐ Inspect and clean spark plug

DATE _____ HOURS _____

123 h
- ☐ Change engine oil
- ☐ Clean oil filter
- ☐ Change oil filter & piston rings
- ☐ Inspect piston

DATE _____ HOURS _____

126 h
- ☐ Inspect and clean spark plug

DATE _____ HOURS _____

SCHEDULE

Inspect and clean spark plug
`Every 21 hours or 500 km`

Change engine oil
`Every 41 hours or 1,000 km`

Clean oil filter
`Every 41 hours or 1,000 km`

Change oil filter & piston rings
`Every 41 hours or 1,000 km`

Inspect piston
`Every 41 hours or 1,000 km`

EVERY RIDE & BY THE CALENDAR

- ☐ **Change engine oil** · After break-in
- ☐ **Inspect engine oil** · Every race
- ☐ **Replace oil filter** · After break-in
- ☐ **Clean and oil air filter** · After break-in
- ☐ **Clean and oil air filter** · Every race
- ☐ **Inspect and clean spark plug** · After break-in

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with Yamaha and accepts no liability for use of this sheet (findmydirtbike.com/terms). Some intervals are converted between hours and miles at an assumed 15 mph.

2005 YAMAHA YZ250F

Garage specs: fluids, plug, chain, tires and torques

FLUIDS

Oil type	20W-40, 10W-30 or 15W-50
Engine oil	1.1 US qt (1.0 L)
Coolant	0.95 US qt (0.9 L)
Fuel capacity	1.85 gal

SPARK PLUG

Spark plug	NGK CR8E
Plug gap	0.028 – 0.031 in (0.7 – 0.8 mm)

CHAIN, SPROCKETS & TIRES

Chain size	520
Chain links	112
Front sprocket	13T
Rear sprocket	48T
Front tire	80/100-21 51M
Rear tire	100/90-19 57M

TORQUE SPECS

Oil drain bolt (crankcase)	15 ft-lb (20 N·m, 2.0 kgf·m)
Oil drain bolt (frame)	17 ft-lb (23 N·m, 2.3 kgf·m)
Oil filter cover bolts	7.4 ft-lb (10 N·m, 1.0 kgf·m)
Spark plug	9.6 ft-lb (13 N·m, 1.3 kgf·m)
Front axle nut	77 ft-lb (105 N·m, 10.5 kgf·m)
Front axle pinch bolts	17 ft-lb (23 N·m, 2.3 kgf·m)
Rear axle nut	92 ft-lb (125 N·m, 12.5 kgf·m)
Upper triple clamp bolts	17 ft-lb (23 N·m, 2.3 kgf·m)
Lower triple clamp bolts	15 ft-lb (20 N·m, 2.0 kgf·m)
Steering stem nut	107 ft-lb (145 N·m, 14.5 kgf·m)
Handlebar clamp bolts	21 ft-lb (28 N·m, 2.8 kgf·m)
Front brake caliper mounting bolts	17 ft-lb (23 N·m, 2.3 kgf·m)
Front brake disc bolts	8.9 ft-lb (12 N·m, 1.2 kgf·m)
Rear brake disc bolts	10 ft-lb (14 N·m, 1.4 kgf·m)
Rear sprocket nuts	31 ft-lb (42 N·m, 4.2 kgf·m)
Front sprocket nut	55 ft-lb (75 N·m, 7.5 kgf·m)
Chain adjuster locknut	12 ft-lb (16 N·m, 1.6 kgf·m)
Shock absorber top mount	41 ft-lb (56 N·m, 5.6 kgf·m)
Shock absorber bottom mount	39 ft-lb (53 N·m, 5.3 kgf·m)
Coolant drain bolt	7.4 ft-lb (10 N·m, 1.0 kgf·m)

For reference only. Compiled from the manufacturer's owner's manual; it may contain errors and is not a substitute for it. Always follow your own manual and a qualified mechanic. FindMyDirtBike is not affiliated with Yamaha and accepts no liability for use of this sheet (findmydirtbike.com/terms). Some intervals are converted between hours and miles at an assumed 15 mph.